


DUALTREAT

HI - PERFORMANCE CONCRETE SEALERS



OVERVIEW - DUALTREAT®
SEALERS & DENSIFIERS

www.dualtreat.com

BECO TREAT APS - Nebelvej 15 - 8700 Horsens (Denmark)

DUALTREAT®

DENSIFIERS

DENSIFIER / DENSIFIER HS HARD / ALL IN ONE



DENSIFIER

USED FOR: Concrete floors to create a dense and dust proof surface.

HIGHLIGHTS:

- Extremely HARD & abrasion resistant SURFACE
- PERMEABILITY REDUCTION to water and chemicals
- Ideally for WAREHOUSES, FACTORIES, CAR PARKS, etc.
- DUST PROOF
- Especially for CONCRETE GRINDING & POLISHING process

COVERAGE RATE: 100-150 ml/m² depending on surface porosity.


DENSIFIER HS HARD with **microFORMULA**® TECHNOLOGY

USED FOR: Troweled, untreated and soft concrete floors. For grinding and polishing processes, where an extreme hardness is required.

HIGHLIGHTS:

- Extremely HARD & abrasion resistant SURFACE
- Excellent CHEMICAL RESISTANCE
- Ideally for WAREHOUSES, FACTORIES, CAR PARKS, etc.
- DUST PROOF
- Can also be used WITHOUT CONCRETE GRINDING & POLISHING process
- EASY & QUICK application

COVERAGE RATE: 100-200 ml/m² depending on surface porosity.



ALL IN ONE with **microFORMULA**® TECHNOLOGY

USED FOR: Concrete floors like steel trowelled, power trowelled, burnished concrete finishes or polished concrete surfaces.

HIGHLIGHTS:

- Good ABRASION RESISTANCE
- Excellent CHEMICAL RESISTANCE
- PROTECTION against grease, oil and water
- DUSTPROOFING
- Open to traffic within ONE HOUR of treatment
- EASY TO CLEAN
- CAN BE POLISHED after application to obtain a higher gloss
- Designed with microFORMULA® technology
- FASTER & MORE COMPLETE BOND reaction than traditional densifiers

COVERAGE RATE: 75-200 ml/m² depending on surface porosity.

DUALTREAT®

SEALERS PROTECTIVE SEALER / PROTECTIVE SEALER SB / REFRESH


PROTECTIVE SEALER

USED FOR: All mineral surfaces like concrete, slate, terracotta, etc.

HIGHLIGHTS:

- Improves FUNCTIONALITY & LOOK of mineral surfaces
- Increased LIFE SPAN
- EASY TO CLEAN
- Water, Oil & Dirt REPELLENT
- Minimizes MOSS & ALGAE growth
- UV-STABLE
- EASY & QUICK application

COVERAGE RATE: 100-200 ml/m² depending on surface porosity.



PROTECTIVE SEALER SB

USED FOR: Polished, dense and non-porous mineral surfaces like marble, granite, etc.

HIGHLIGHTS:

- Improves FUNCTIONALITY & LOOK of non-porous mineral surfaces
- Increased LIFE SPAN
- EASY TO CLEAN
- Water, Oil & Dirt REPELLENT
- Minimizes MOSS & ALGAE growth
- UV-STABLE
- EASY & QUICK application

COVERAGE RATE: 50-100 ml/m² depending on surface porosity.

DUALTREAT®

MAINTENANCE REFRESH

REFRESH for Maintenance

USED FOR: Surfaces previously treated with DUALTREAT®.

HIGHLIGHTS:

- MAINTAINS sustainably treated concrete floors
- Designed for HIGH people and machinery TRAFIC
- Improves FUNCTIONALITY & LOOK of concrete surfaces
- UV-STABLE

COVERAGE RATE: 75-100 ml/m² depending on surface porosity.

