



ELECTRIC MODEL

Œ

Horsepower	15 KW
Voltage (50/60 Hz)*	3 ph x 380-400V
Amperage (max)	32 Amp
Dedicated Breaker Requirement	32 Amp
Weight of Machine	660 kg
Grinding Pressure Weights Pos. 1	245 kg
Grinding Pressure Weights Pos. 2	296 kg
Grinding Pressure Weights Pos. 3	340 kg
Grinding Pressure Weights Pos. 4	395 kg
Grinding Pressure Weights Pos. 4 Attachment Speed	395 kg 300-1100 rpm
Attachment Speed	300-1100 rpm
Attachment Speed Working Width	300-1100 rpm 814 mm
Attachment Speed Working Width Tool Holder Diameter	300-1100 rpm 814 mm 3x225 mm
Attachment Speed Working Width Tool Holder Diameter Vacuum Hose Port	300-1100 rpm 814 mm 3x225 mm Camlock E300 Peripheral & Front
Attachment Speed Working Width Tool Holder Diameter Vacuum Hose Port Water feeding (with pump)	300-1100 rpm 814 mm 3x225 mm Camlock E300 Peripheral & Front Mist
Attachment Speed Working Width Tool Holder Diameter Vacuum Hose Port Water feeding (with pump) Water tank capacity	300-1100 rpm 814 mm 3x225 mm Camlock E300 Peripheral & Front Mist 46 L

L32EU

*Also offered with 335-mm heads - L3213EU

- DUST-PROOF GRINDING HEAD WITH LOW-FRICTION CHAIN GEAR PLANETARY DRIVE
- DUST SUPPRESSION FINE MISTING SYSTEM WITH HIGH
 PRESSURE SPRAY NOZZLES
- EASY-TO-USE INTEGRATED WEIGHTS
- IMPROVED DUST COLLECTION EFFICIENCY
- ADDED PROTECTION AGAINST EXCESSIVE VOLTAGE
- LED LIGHTS IN FRONT & BACK
- NEW ADJUSTABLE HANDLE BAR
- CHARGING PHONE STATION WITH DUAL USB 2.0 PORTS
- A DURABLE STAINLESS STEEL CUP HOLDER

The grinding heads are now with counter-clockwise rotation. Use the BLUE pcd's and carbide scrapers.



