

SERIES

REMOTE-CONTROLLED MODEL



The grinding heads are now with counter-clockwise rotation. Use the BLUE pcd's and carbide scrapers.





L32REU

*Also offered with 335-mm heads - L3213REU



Horsepower	15 KW
Voltage (50/60 Hz)	3ph x 380-400V
Amperage (max)	32 Amp
Dedicated Breaker Requirement	32 Amp
Weight of Machine	683 kg
Grinding Pressure Weights Pos. 1 Grinding Pressure Weights Pos. 2	245 kg 296 kg
Grinding Pressure Weights Pos. 3 Grinding Pressure Weights Pos. 4	340 kg 395 kg
Attachment Speed	300-1100 rpm
Working Width	814 mm
Tool Holder Diameter	3x225 mm
Vacuum Hose Port	Camlock E300
Water feeding (with pump)	Peripheral & Front Mist
Water tank capacity	46 L
Cable Length	17.4 m
AMG Battery RC Battery (rechargeable)	12 V/2x7 AH AA 1.2V
,	

See back page for more features.

L32REU

NEW INTELLIGENT REMOTE CONTROL

Precise control over the machine - two sensitive thumbsticks control its position and offset, including integrated mapping on the offset. A wide range of functions. Super light and easy to use with ergonomic rubber grip.

INTUITIVE TOUCHSCREEN PANEL / HMI

Our new HMI provides essential operating information and implements operators' instructions. It can be used in 3 modes: remote-controlled, self-propelled and manual.

HMI functionality includes:

- indications of power supply and power consumption,
- · machine load and hours worked,
- tool holder rpm and option to choose rpm setting with tool input,
- · water supply and lights activation,
- maintenance reminders,
- password activation and shuto, etc.














- DUST-PROOF PLANETARY DRIVE
- DUST SUPPRESSION FINE MISTING SYSTEM WITH HIGH PRESSURE SPRAY NOZZLES
- ADDED PROTECTION AGAINST EXCESSIVE VOLTAGE
- EASY-TO-USE INTEGRATED WEIGHTS
- IMPROVED DUST COLLECTION EFFICIENCY
- LED LIGHTS IN FRONT & BACK
- NEW ADJUSTABLE HANDLE BAR
- CHARGING PHONE STATION WITH USB
- A DURABLE STAINLESS STEEL CUP HOLDER
- HEAVY-DUTY THIRD WHEEL AND LARGE SOLID RUBBER TIRES